

PRODUCT SPECIFICATION FORM

HARRINGTON ELECTRIC WIRE ROPE PRODUCTS

RH / RHA THREE-PHASE ELECTRIC WIRE ROPE HOISTS/TROLLEYS

Quantity _____
 Capacity _____
 Lift _____
 Headroom Needed _____
 Configuration D (Deck/Base Mounted or Lug Suspended Hoist)
 S (Standard Headroom Trolley Hoist)
 U (Ultra-Low Headroom Trolley Hoist)
 Hoist Speed _____ Single _____ Dual
 Trolley Speed _____ Single - 40 FPM 64 FPM 80 FPM
 Dual - 64/16 FPM 80/20 FPM
 Voltage _____ 230-3-60 _____ 460-3-60
 Control Voltage 110V
 Beam Type/Size _____
 Beam Flange Width _____
 Beam Radius _____ (if curved monorail)

Options:

Special Voltage _____
 Pendant and Pendant Cord
 Specify Drop _____
 Choose Unwired Installed
 Power Supply Cord
 Specify Length _____
 Choose Unwired Installed
 Eye Bolt Kit
 Trolley Travel Limit Switch
 Weatherization (for outdoor use)

Specials: _____

Please contact Harrington's Customer Service Department for further assistance:

Location	Phone Number	Fax Number
Manheim, PA	800-233-3010	717-665-7432
Corona, CA	800-317-7111	951-279-7500

E-mail: customerservice@harringtonhoists.com

Form completed by:

Name _____ Company _____

Phone _____ Fax _____